



# Intelligent Blocker Ice 900

The Ice 900 is NIDEK's Automatic Blocker, which complements the NIDEK Lens Edger line-up. It boasts high accuracy, easy viewing and swift operation.

## Graphic Design



"Smart screen" design provides the operator with an information bar and on-screen tutorial for ease of use. In addition, layout and grinding conditions are easily entered on the color-coded 8.4-inch SVGA touch screen display.

## Quick Twin Jog Dial




In addition to the intuitive operation of touch screen, data can also be entered by the use of the twin "quick jog" dials. The left jog dial moves the cursor for layout and grinding condition selection, while the right jog dial is used to enter numerical values/changes.

## Tiltable Display



A unique tiltable display allows the LCD operation screen to be viewed at four different angles, making it ergonomically friendly whether in a sitting or standing position.

## Shape Editor Function



This function allows the operator to freely design lens shapes with the use of a stylus pen, while still viewing the original lens shape. The background displays a rendition of a human face (eye and nose) in three varying forms: woman, man and child. Therefore, the operator can edit the shape of the lens while viewing it in relation to the face of a "virtual patient".

## Data Management



The data management feature allows storing, searching, and recalling of traced data. A maximum of 30,000 patterns can be saved. Data can also be saved to a USB flash drive (optional).

## Motor Drive Blocking




The motorized lens blocking process takes only two seconds, greatly increasing productivity. Since excessive blocking pressure can cause lens coating deterioration when the block is removed, the Ice 900 applies the appropriate blocking pressure, and protects lens from the damaging. In addition, the block adapter is ideally positioned for easy and comfortable block loading.

## Flexible Lens Stage



The flexible lens stage continuously applies upward stabilizing pressure, keeping the front base curve of the lens at the optimal horizontal position. In turn, the stabilization of the blocking surface yields the highest blocking precision.

## Integrated Shape Imager (ISI)



The ISI function detects any demo lens or pattern, including those for rimless drill mounts, and identifies hole position. Moreover, the ISI function automatically compensates horizontal axis. The operation is supported by a "Wizard Tutorial" directly viewed on the screen of the unit, featuring user-friendly instruction.

## Partial Step Measurement



The optional partial step package provides automatic measurement of the partial step data of the demo lens. With partial step edging of the Multifunction Edger Me 1200\*, the partial step package allows the prescribed spectacle lenses to be mounted into the frame of sports sunglasses, and helps to meet the request of a demanding customer.

\* Available for PLB-8S and PLB-2R8S types

## Accessory Tray



An accessory tray is provided to store small items. The Integrated Shape Imager table, spare fuses, and small-diameter lens holder are all stored under the tray.

## System Configurations

The Ice 900 can be connected to any of NIDEK's lens edgers in a multitude of configurations.

## Ice 900 Specifications

Lens size	Dia. 85 mm or less
Layout span	FPD : 30.00 to 99.50 mm PD (or 1/2 PD) : 30.00 to 99.50 mm (15.00 to 49.75 mm) Height of the optical center : 0 to ±15 mm Size adjustment : 0 to ±9.95 mm WD : 15.0 to 45.0 mm EP : 0.0 to 6.0 mm
Item to be entered	FPD (or DBL) PD (or 1/2 PD) Height of the optical center (BT height and PD height can be selected) Lens size Lens material (Plastic, Plastic lens with high refractive index, Glass, Polycarbonate, Acrylic, Trivex, Polyurethane) Frame type (Metal, Celluloid, Nylon, Two point) Grinding mode selection Lens type (Single, Multi (Bifocal), Prog. (Progressive)) Job code
Shape imager function	Measurement range : 65.5 x 49.0 mm (±1.5 mm)* Hole position : 0.01 mm increments Hole diameter : ø0.50 to 1.00 mm (0.01 mm increments)
Blocking method	Motor drive
Display	8.4-inch SVGA color LCD touch panel
Interface	4 RS-232C, 1 LAN (10 / 100 Base-T)
Power supply	AC 100 to 120 V / 230 V 50 / 60 Hz
Power consumption	50 VA
Dimensions / Mass	256 (W) x 367 (D) x 352 (H) mm / 8 kg 10.1 (W) x 14.4 (D) x 13.9 (H) " / 17.6 lbs.
Standard accessories	Spare fuse, Interface cable, Stylus pen, Power cord, Lens table for shape imager, Small-diameter lens holder
Optional accessories	Barcode scanner, USB flash drive, Partial step package

\* 80.0 x 55.0 mm (±1.5 mm) for partial step measurement. Some part of the lens can't be measured.

Specifications and design are subject to change without notice.  
Trivex is a registered trademark of PPG Industries Ohio, Inc.



**HEAD OFFICE**  
**(International Div.)**  
34-14 Maehama, Hiroishi  
Gamagori, Aichi 443-0038,  
JAPAN  
TEL: +81-533-67-8895  
URL: <http://www.nidek.com>  
[Manufacturer]

**TOKYO OFFICE**  
**(International Div.)**  
3F Sumitomo Fudosan Hongo  
Bldg., 3-22-5 Hongo, Bunkyo-ku,  
Tokyo 113-0033, JAPAN  
TEL: +81-3-5844-2641  
URL: <http://www.nidek.com>

**NIDEK INC.**  
47651 Westinghouse Drive,  
Fremont, CA 94539, U.S.A.  
TEL: +1-510-226-5700  
+1-800-223-9044  
(US only)  
URL: <http://usa.nidek.com>

**NIDEK S.A.**  
Europarc,  
13 rue Auguste Perret,  
94042 Créteil, FRANCE  
TEL: +33-1-49 80 97 97  
URL: <http://www.nidek.fr>

**NIDEK TECHNOLOGIES S.R.L.**  
Via dell'Artigianato,  
6/A, 35020 Albignasego (Padova),  
ITALY  
TEL: +39 049 8629200/8626399  
URL: <http://www.nidektechnologies.it>

**NIDEK (SHANGHAI) CO., LTD.**  
Rm3205, Shanghai Multi  
Media Park, No.1027 Chang  
Ning Rd, Chang Ning District,  
Shanghai, CHINA 200050,  
TEL: +86 021-5212-7942  
URL: <http://www.nidek-china.cn>

**NIDEK SINGAPORE PTE. LTD.**  
51 Changi Business Park  
Central 2, #06-14, The  
Signature 486066,  
SINGAPORE  
TEL: +65 6588 0389